



Kleeschulte wood fibre topora®



wood fibre topora®



Application and Characteristics:

- Balanced air holding capacity
- Improved drainage
- Very good and fast re-wettability and water take in after drying out even in mixtures of black peat or compost
- Excellent air filled porosity
- Significantly less shrinkage than peat
- Stable consistency/structure
- Aiding effect on formation and growth of roots
- Acceptance by consumer because of earthy colour and natural look
- Available all year round in constant quality
- Reproducible quality because of standardized production methods
- Availability irrespective of weather conditions
- Free from weeds
- Consistent and even growth
- Good technical handling characteristics during manufacturing
- Light aggregate / Low bulk density for low transport cost
- **Wood fibre topora®** is very suited for mixing with black peat and composts (up to 30 % is recommended)
- **Wood fibre topora®** is available in various qualities such as fine/medium or coarse

Product accreditation:

- Meets the criteria of the RAL-Quality assurance wood fibre of Quality assurance Association Substrates for Plants

nutrient content

pH-Wert (Ca Cl ₂):	5.5
salt content:	0,50 g/l
N:	50 mg/l
P ₂ O ₅ :	50 mg/l
K ₂ O:	< 100 mg/l
water-capacity:	35 Vol-%
dimensional weight:	105 g/l
N-immobilisation:	135 mgN/l

Delivery units:
250 - 300 EN m³ per truck